

PRE-DELIVERY/ANNUAL/FREQUENT INSPECTION CHECKLIST

Model: _____

Serial No. _____

- Check each item listed below
- Use proper operating, service, and maintenance manual for specific information and settings
- If an item is found to be unacceptable make the necessary repairs and check the "repaired" box
- When all items are "acceptable", the unit is ready for service



WORK PLATFORMS SHALL BE INSPECTED, SERVICED, AND ADJUSTED TO MANUFACTURER'S REQUIREMENTS BY A QUALIFIED MECHANIC PRIOR TO EACH SALE, LEASE, OR RENTAL, AND EVERY 3 MONTHS OR 150 HOURS, WHICHEVER COMES FIRST, AND ANNUALLY.

Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A-Not Applicable	Y	N	R	N/A
BASE:				
No broken welds				
Inspect slide tracks for damage				
All frame bolts tight				
Pump secure				
DC drive motors secure				
Batteries fully charged				
Tie rods secure (Pro Series)				
WHEELS:				
Snap rings secure				
Bolts/nuts tight				
SCISSORS:				
No broken welds				
No bent beam members				
All rollers turn freely				
Retaining rings secure on pivots				
Maintenance locks: Stored and securely connected				
Scissor beam tube bolts tight				
PLATFORM:				
No bent rails				
No broken welds				
All rails in place/secure				
110V outlet safe/working				
Entrance gate closes freely				

Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A-Not Applicable		Y	N	R	N/A
DECALS:					
Legible					
Correct capacity noted					
Proper placement & quantity					
RAILS/EXTENDING PLATFORM:					
Extends freely					
Cables in place/secure					
Locks in stowed position					
Locks in extended position					
FUNCTIONS:					
All functions (drive, elevate, and steer) operational (see Pre-Start Inspection for details)					
Pothole guards deploy when platform elevated					
Emergency stop breaks circuits					
Slow speed mode activates just after units pothole bars are deployed					
Pothole interlock functions correctly					
BRAKES:					
Operational					
EMERGENCY DOWN:					
Operational					
WIRING:					
Switches secure					
Contactor(s) secure					
Tight on terminals (No loose wiring)					
OIL:					
Level 1" from top (when platform stowed)					
OTHER:					
Check all hoses for leaks					
Check all fittings for leaks					
Battery charger secure/operational					
When tilted past the allowable degree, unit will not elevate					
Warning horn					
Hour meter operational					
Battery indication operational					
Operator's Manual is on the unit					
Overload light & alarm sounds when overloaded (Only required for annual inspection on CE Lifts)					
DATE:	INSPECTED BY:				